BEST AVAILABLE COPY

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 30 June 2005 (30.06.2005)

(10) International Publication Number WO 2005/058720 A1

(51) International Patent Classification7:

B65D 41/04

(21) International Application Number:

PCT/GB2004/005099

(22) International Filing Date: 3 December 2004 (03.12.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 0329444.4

19 December 2003 (19.12.2003)

(71) Applicant (for all designated States except US): BEESON AND SONS LIMITED [GB/GB]; Hertford Place, Denham Way, Rickmansworth WD3 2XB (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): KING, Roger, Milner [GB/GB]; White End Park Farm, Latimer, Buckinghamshire HP5 1UL (GB).

(74) Agents: JAMES, Anthony, Christopher, W., P. et al.; Carpmaels & Ransford, 43-45 Bloomsbury Square, London WC1A 2RA (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW. GH. GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: BOTTLE AND CLOSURE ASSEMBLY WITH IMPROVED LOCKING ELEMENTS



neck, the closure having a base portion (22) and a skirt portion (24); a first screw thread on the neck, said first screw thread comprising one or more first thread segments (16), and a second screw thread on an inner surface of the skirt of the closure, said second screw thread comprising one or more second thread segments (26); a first locking projection (44) on the container neck separate from the first thread segments (16) and a second locking projection (46) on the inner surface of the skirt of the closure separate from the second thread segments (26), said first and second locking projections being configured to resist unscrewing of the closure from the fully engaged position on the container neck after the closure has been secured or resecured on the container neck until a predetermined minimum opening torque is applied; wherein said first and second locking projections (44, 46) longitudinally overlap the first or the second thread segments when the closure is in the fully engaged position on the container neck.